

**IOS INTERCHANGEABLE OPTICAL SYSTEM**  
 99.99% pure aluminium reflector; twist lock fixing system;  
 tempered safety glass (clear, microsphere or shaped);  
 4 beams available: narrow, medium, wide, narrow and long.



# LADDER

**pendant with IOS optics  
 adjustable via universal joint  
 for metal halide lamps, 35W/70W G 12**

In order to achieve the desired lighting configuration, the luminaire is supplied without IOS optics. When ordering, the luminaire code no., the IOS optics code no. must be indicated.

**Body** painted steel with die-cast aluminium tilting optics.  
 4 steel suspension cables

**Adjustment** horizontal 356° - vertical 50°

**Control gear technologies** HF control gear (housed in the central body)




**Installation** ceiling mounted










www.reggiani.net/code no.



**Standard finishes** .10 white .28 metallised grey



	CONTROL GEAR	W		IP
<b>S5218</b>	HF	2 x 35	CDM-T	G 12 20
<b>S5219</b>	HF	2 x 70	CDM-T	G 12 20
<b>S5220</b>	HF	4 x 35	CDM-T	G 12 20
<b>S5221</b>	HF	4 x 70	CDM-T	G 12 20
<b>S5222</b>	HF	6 x 35	CDM-T	G 12 20
<b>S5223</b>	HF	6 x 70	CDM-T	G 12 20



Can be purchased separately in the desired finish in order to change the width and colour of the light beam

**3305** 2x 6° / 7° / 8°  
**3306** 2x 11° / 12° / 12°  
**3307** 2x 37° / 39° / 41°

**3308** IOS MIRA

FINISHES: .00 CLEAR, .59 I R, .79 ANTI UV, .65 BLUE SELECTIVE FILTER, .66 RED SELECTIVE FILTER, .67 PINK SELECTIVE FILTER, .74 BLUE DICHROIC, .75 GREEN DICHROIC, .76 YELLOW DICHROIC, .77 RED DICHROIC



INTERCHANGEABLE OPTICAL SYSTEM

