

IEC SYSTEM FOR MUTUAL RECOGNITION OF
TEST CERTIFICATES FOR ELECTRICAL
EQUIPMENT (IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product
Produit

Name and address of the applicant
Nom et adresse du demandeur

Name and address of the manufacturer
Nom et adresse du fabricant

Name and address of the factory
Nom et adresse de l'usine

*Note: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2^{ème}
page*

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

Trademark (if any)
Marque de fabrique (si elle existe)

Recessed luminaires

REGGIANI S.P.A. ILLUMINAZIONE
Viale Monza 16
I-20845 Sovico (MB)
Italy

REGGIANI S.P.A. ILLUMINAZIONE
Viale Monza 16
I-20845 Sovico (MB)
Italy

Additional information on page 2
REGGIANI S.P.A. ILLUMINAZIONE
Viale Monza 16
I-20845 Sovico (MB)
Italy

1x34 W Ceramic CoB LEDs, 950 mA, 37 Vdc max, IP20/IP44, Class III,
used SELV source



Type of Manufacturer's Testing Laboratories
used
Type de programme du laboratoire d'essais
constructeur

Model / Type Ref.
Ref. De type

Additional information (if necessary may also be
reported on page 2)
Les informations complémentaires (si
nécessaire, peuvent être indiqués sur la 2^{ème}
page

A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a
été
considéré conforme à la

As shown in the Test Report Ref. No. which
forms part of this Certificate
Comme indiqué dans le Rapport d'essais
numéro de référence qui constitue partie de ce
Certificat

Series MOOD ADJUSTABLE
cod X.KG17H.NN

Additional information on page 2
Refers to CB Test Report for the entire list of rating covered by the certificate

IEC 60598-1:2014
IEC 60598-2-2:2011
National differences:
EU Group Differences

3504696.54

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme National de Certification

Meander 1051, NL-6825 MJ Arnhem, Netherlands
DEKRA Certification B.V.



Firmato digitalmente da
MASSIMILIANO TRIULZI

Code	Insulation class	IP degree	Type installation	t _a
cod X.xy.z	III	IP 20 recessed part IP44 exposed part	Recessed ceiling	25 °C

LEGEND

x	Type of luminaire	GG11 = Mood S adjustable flush round visible trim 3,5W LG11 = Mood S adjustable flush round trimless 3,5W MG11 = Mood S adjustable flush square visible trim 3,5W PG11 = Mood S adjustable flush square trimless 3,5W GG12 = Mood M adjustable flush round visible trim 8,5W LG12 = Mood M adjustable flush round trimless 8,5W HG12 = Mood M adjustable cone round visible trim 8,5W KG12 = Mood M adjustable cone round trimless 8,5W MG12 = Mood M adjustable flush square visible trim 8,5W PG12 = Mood M adjustable flush square trimless 8,5W NG12 = Mood M adjustable pyramid square visible trim 8,5W QG12 = Mood M adjustable pyramid square trimless 8,5W GG13 = Mood L adjustable flush round visible trim 12W LG13 = Mood L adjustable flush round trimless 12W HG13 = Mood L adjustable cone round visible trim 12W KG13 = Mood L adjustable cone round trimless 12W MG13 = Mood L adjustable flush square visible trim 12W PG13 = Mood L adjustable flush square trimless 12W NG13 = Mood L adjustable pyramid square visible trim 12W QG13 = Mood L adjustable pyramid square trimless 12W GG14 = Mood L adjustable flush round visible trim 17W LG14 = Mood L adjustable flush round trimless 17W HG14 = Mood L adjustable cone round visible trim 17W KG14 = Mood L adjustable cone round trimless 17W MG14 = Mood L adjustable flush square visible trim 17W PG14 = Mood L adjustable flush square trimless 17W NG14 = Mood L adjustable pyramid square visible trim 17W QG14 = Mood L adjustable pyramid square trimless 17W GG15= MoodXL adjustable flush round visible trim 22W LG15 = Mood XL adjustable flush round trimless 22W HG15= Mood L adjustable cone round visible trim 22W KG15 = Mood L adjustable cone round trimless 22W MG15= Mood L adjustable flush square visible trim 22W PG15= Mood L adjustable flush square trimless22W NG15= Mood L adjustable pyramid square visible trim 22W QG15 = Mood L adjustable pyramid square trimless 22W GG16= Mood XL adjustable flush round visible trim 25W
---	-------------------	--

x	Type of luminaire	<p>LG16 = Mood XL adjustable flush round trimless 25 W HG16= Mood XL adjustable cone round visible trim 25 W KG16 = Mood XL adjustable cone round trimless 25 W MG16= Mood XL adjustable flush square visible trim 25 W PG16= Mood XL adjustable flush square trimless 25 W NG16= Mood XL adjustable pyramid square visible trim 25 W QG16 = Mood XL adjustable pyramid square trimless 25W GG17= Mood XL adjustable flush round visible trim 34 W LG17 = Mood XL adjustable flush round trimless 34 W HG17= Mood XL adjustable cone round visible trim 34 W KG17 = Mood XL adjustable cone round trimless 34 W MG17= Mood XL adjustable flush square visible trim 34 W PG17= Mood XL adjustable flush square trimless 34 W NG17= Mood XL adjustable pyramid square visible trim 34 W QG17 = Mood XL adjustable pyramid square trimless 34W</p>
y	Type of optical reflector	<p>B = narrow beam D = medium-narrow beam E = medium beam H = wide beam</p>
z	Colour temperature	<p>WW = 3000 K, CRI >80 HQ = 3000 K, CRI > 90 HW = 2700 K, CRI > 90 NN = 4000 K, CRI > 80 DT = 2000 K-3000 K, CRI > 95 XW = 2700 K, CRI > 95 XQ = 3000 K, CRI > 95 XN = 4000 K, CRI > 95</p>