


IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE


Product	Fixed general purpose luminaires
Name and address of the applicant	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Name and address of the manufacturer	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Name and address of the factory	<input type="checkbox"/> Additional information on page 2 REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	220-240 V~, 50/60 Hz, Class I, IP40
Trademark (if any)	
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	cod D.BH250.WW
Additional information (if necessary may also be reported on page 2)	<input type="checkbox"/> Additional information on page 2 Refers to CB Test Report for the entire list of rating covered by the certificate
A sample of the product was tested and found to be in conformity with	IEC 60598-1:2014, IEC 60598-2-1:1979, IEC 60598-2-1:1979/AMD1:1987 National differences: EU Group Differences
As shown in the Test Report Ref. No. which forms part of this Certificate	3505211.51

This CB Test Certificate is issued by the National Certification Body

DEKRA Certification B.V.
Meander 1051, NL-6825 MJ Arnhem, Netherlands

Firmato digitalmente da

MASSIMILIANO TRIULZI



Code	Insulation class	Colour temperature	IP degree	t _a
cod x.yH2z0.w	I	2700 K CRI>90= HW 3000 K CRI>90 = HQ 3000 K CRI>80 = WW 4000 K CRI>80 = NN	IP40	25 °C

LEGEND

x	Type of control	<p>0 = Not dimmable F = DALI ready to mains system D = DALI</p>
y	Type of luminaire	<p>B = With end caps, with diffusive screen C = With end cap and male connector, with diffusive screen D = Female connector and male connector, with diffusive screen F = Female connector and end cap, with diffusive screen N = With end caps, with Louver screen (UGR<19) P = With end cap and male connector, with Louver screen (UGR<19) Q = Female connector and male connector, with Louver screen (UGR<19) R = Female connector and end cap, with Louver screen (UGR<19) G = With end caps, with prismatic screen H = With end cap and male connector, with prismatic screen L = Female connector and male connector, with prismatic screen M = Female connector and end cap, with prismatic screen K = With end caps, with ribbed screen, W = With end cap and male connector, with ribbed screen X = Female connector and male connector, with ribbed screen Y = Female connector and end cap, with ribbed screen T = With end caps, with very diffusing screen U = With end cap and male connector, with very diffusing screen V = Female connector and male connector, with very diffusing screen Z = Female connector and end cap, with very diffusing screen</p>
z	Type of rating	<p>2 = 13 W 100 mA 149 V max, length module 460 mm (2x) 5 = 26 W 200 mA 149 V max, length module 920 mm (4x) 7 = 38 W 300 mA 149 V max, length module 1380 mm (6x)</p>
w	Type colour temperature and CRI	<p>HW = 2700 K CRI>90 HQ = 3000 K CRI>90 WW = 3000 K CRI>80 NN = 4000 K CRI>80</p>