

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product Produit	Recessed luminaires
Name and address of the Applicant Nom et adresse du demandeur	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 I-20845 Sovico (MB) Italy
Name and address of the manufacturer Nom et adresse du fabricant	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 I-20845 Sovico (MB) Italy
Name and address of the factory Nom et adresse de l'usine	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 I-20845 Sovico (MB) Italy
Rating and principal characteristics Valeurs nominales et caractéristiques principales	1x 10 W Ceramic Cob LEDs, 39 Vmax, 0,26 A , Class III, IP20 recessed part IP65 exposed part Refer to ANNEX 1 for the entire list of rating covered by the certificate
Trademark (if any) Marque de fabrique (si elle existe)	Reggiani S.p.A.
Type of manufacturer's Testing Laboratories used Type de programme de laboratoire d'essais constructeur	
Model / Type Ref. Réf. de type	cod X.CE32K
Additional information (if necessary may also be reported on page 2) Les informations complémentaires (si nécessaire, peuvent être indiquées sur la 2ème page)	Refer to ANNEX 1 for the entire list of models covered by the certificate
A sample of product was tested and found to be in conformity with IEC Un échantillon de ce produit a été essayé et été considéré conforme à la CEI	60598-1(ed.8) 60598-2-2(ed.3)
National differences / Comments Les différences nationales / Commentaires	EU Group Differences
As shown in the test report Ref. No. which forms part of this certificate Comme indiqué dans le rapport d'essais numéro de référence qui constitue partie de ce certificat	3504166.63

This CB Test Certificate is issued by the National Certification Body:

DEKRA Certification B.V.
Meander 1051, 6825 MJ
Arnhem
The Netherlands

Ce Certificat d'essai OC est établi par l'Organisme National de Certification



Date: 2015-06-04

Signature: M.Triulzi



Code	Insulation class	Colour temperature	t _a
cod x.yE32z	III	2700 K = HW 3000 K = HQ 3000 K = WW 4000 K = NN	25 °C

LEGEND

x	Type of luminaire	X= without controlgear
y	Type of the luminaire	V = Recessed hole 60 mm IP20 / IP65 (external part) U = Recessed hole 66 mm IP20 / IP23 (external part) R = Recessed hole 73 mm IP20 / IP23 (external part) T = Recessed hole 73 mm IP20 / IP23 (external part) H = Recessed hole 60 mm IP20 / IP43 (external part) M = Recessed hole 90 mm IP20 / IP23 (external part) N = Recessed hole 105 mm IP20 / IP23 (external part) P = Recessed hole 105 mm IP20 / IP23 (external part) G = Recessed hole 82 mm IP20 / IP43 (external part) L = Recessed hole 90 mm IP20 / IP23 (external part) C = Recessed hole 86 mm IP20 / IP65 (external part) B = Recessed hole 80 mm IP20 / IP23 (external part) D = Recessed hole 65 mm IP20 / IP43 (external part) F = Recessed hole 82 mm IP20 / IP43 (external part)
z	Type of optical reflector	1 = with optical reflector cod 0.35005.0000 narrow beams 2 = with optical reflector cod 0.35006.0000 medium beams 3 = with optical reflector cod 0.35007.0000 wide beams K = without optical reflector