



Ref. Certif. No.

DK-41568-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST  
CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEMESYSTEME CEI D'ACCEPTATION MUTUELLE DE  
CERTIFICATS D'ESSAIS DES EQUIPEMENTS  
ELECTRIQUES (IECEE) METHODE OC

## CB TEST CERTIFICATE

Product  
ProduitName and address of the applicant  
Nom et adresse du demandeurName and address of the manufacturer  
Nom et adresse du fabricantName and address of the factory  
Nom et adresse de l'usineNote: When more than one factory, please report on page 2  
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2<sup>ème</sup> pageRatings and principal characteristics  
Valeurs nominales et caractéristiques principalesTrademark (if any)  
Marque de fabrique (si elle existe)  
Type of Manufacturer's Testing Laboratories used  
Type de programme du laboratoire d'essais  
constructeurModel / Type Ref.  
Ref. De typeAdditional information (if necessary may also be  
reported on page 2)  
Les informations complémentaires (si nécessaire,,  
peuvent être indiqués sur la 2<sup>ème</sup> pageA sample of the product was tested and found  
to be in conformity with  
Un échantillon de ce produit a été essayé et a été  
considéré conforme à laAs shown in the Test Report Ref. No. which forms part  
of this Certificate  
Comme indiqué dans le Rapport d'essais numéro de  
référence qui constitue partie de ce Certificat

## CERTIFICAT D'ESSAI OC

Recessed luminaires

REGGIANI SPA ILLUMINAZIONE  
VIALE MONZA 16  
SOVICO, 20845 MB ItalyREGGIANI SPA ILLUMINAZIONE  
VIALE MONZA 16  
SOVICO, 20845 MB ItalyREGGIANI SPA ILLUMINAZIONE  
VIALE MONZA 16  
SOVICO, 20845 MB Italy☐ Additional Information on page 2220-240 V~, 50/60 Hz, 1x 30 W ceramic Cob LEDs, Class II, IP20  
See Page 2

Reggiani S.p.A

See Page 2

Additionally evaluated to EN 60598-1:2008/ A11:2009 and EN  
60598-2-2:2012; National Differences specified in the CB Test  
Report.☐ Additional Information on page 2

IEC 60598-1(ed.7), IEC 60598-2-2(ed.3)

4786526355-4 issued on 2014-10-13

This CB Test Certificate is issued by the National Certification Body  
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**

- ☐ UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☒ UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☐ UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2014-10-22

Signature:

Jan-Erik Storgaard



Ref. Certif. No.

DK-41568-UL

## Model Details:

| Code        | Supply voltage [V] | Hz    | Insulation class | Colour temperature                           | Iout max [mA] | Pmax [W] | IP degree | ta   |
|-------------|--------------------|-------|------------------|--|---------------|----------|-----------|------|
| cod x.yD92z | 220-240~           | 50/60 | II               | 2700K HW<br>3000K HQ<br>3000K WW<br>4000K NN | 260           | 10       | IP20      | 25°C |
| cod x.yD93z | 220-240~           | 50/60 | II               | 2700K HW<br>3000K HQ<br>3000K WW<br>4000K NN | 350           | 13       | IP20      | 25°C |
| cod x.yD95z | 220-240~           | 50/60 | II               | 2700K HW<br>3000K HQ<br>3000K WW<br>4000K NN | 600           | 22       | IP20      | 25°C |
| cod x.yD97z | 220-240~           | 50/60 | II               | 2700K HW<br>3000K HQ<br>3000K WW<br>4000K NN | 800           | 30       | IP20      | 25°C |

## LEGEND

|   |                           |   |
|---|---------------------------|---|
| x | Type of control           | 0 = Not dimmable<br>T = Cut Phase<br>V = 1-10 V<br>D = DALI   |
| y | Type of projector         | B = round trimless recessed projector<br>C = round recessed projector with bezel<br>D = square trimless recessed projector<br>F = square recessed projector with bezel<br>G = oval trimless recessed projector<br>H = oval recessed projector with bezel<br>L = rectangular trimless recessed projector<br>M = rectangular recessed projector with bezel<br>N = Semi-recessed ceiling mounted projector (recessed hole 110mm)<br>R = Semi-recessed ceiling mounted projector (recessed hole 55mm)   |
| z | Type of optical reflector | K = without optical reflector<br>A = with optical reflector cod 0.35049.0000 satin very narrow beams<br>B = with optical reflector cod 0.35050.0000 very narrow beams<br>C = with optical reflector cod 0.35051.0000 narrow beams<br>D = with optical reflector cod 0.35052.0000 medium beams<br>E = with optical reflector cod 0.35053.0000 wide beams<br>F = with optical reflector cod 0.35054.0000 Mira<br>1 = with optical reflector cod 0.35005.0000 narrow beams<br>2 = with optical reflector cod 0.35006.0000 medium beams<br>3 = with optical reflector cod 0.35007.0000 wide beams |

## Additional information (if necessary)

## Information complémentaire (si nécessaire)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2014-10-22

Signature:

Jan-Erik Storgaard