


New

Track


EN

Reggiani


The most
flexible
standard
track we have
ever had




3-circuit track



3-circuit track +
Control system
(DALI / DIMM 1-10V DC)



New




Track

New


Track

This new universal track system adapts to every present and future need. The range uses 6-conductor technology for the three circuits and the control system, now integrated into a single product.

The track includes the surface-mounted and recessed version plus a range of accessories to make installation even more flexible and simple. The streamlined, elegant design and exceptional adaptability make it the perfect complement for our track-mounted projectors and linear luminaires.



Surface-mounted track



Finishes:



White

10



Black


21



Metallised
grey




28

Recessed track



VERSIONS




Surface-mounted track



Track length		Finishes	
0.02030.00	1000 mm	10	White
0.02031.00	2000 mm	21	Black
0.02032.00	3000 mm	28	Metallised grey
0.02033.00	4000 mm		

Code example: **0.02030.00 10**

Recessed track




Track length		Finishes	
0.02034.00	1000 mm	10	White
0.02035.00	2000 mm	21	Black
0.02036.00	3000 mm	28	Metallised grey
0.02037.00	4000 mm		


Code example: **0.02034.00 10**

ELECTROMECHANICAL CONNECTIONS

Live end feed



0.02038.00




0.02039.00

Type	
0.02038.00	Earth right
0.02039.00	Earth left

Finishes	
10	White
21	Black
28	Metallised grey

Code example: 0.02038.00 10


Straight connector



Finishes	
10	White
21	Black
28	Metallised grey

Code example: 0.02040.00 10

Live middle feed




Finishes	
10	White
21	Black
28	Metallised grey


Code example: 0.02042.00 10

Technical drawings - top view

L-connector



0.02043.00




0.02044.00

Type	
0.02043.00	Earth outside
0.02044.00	Earth inside


Finishes	
10	White
21	Black
28	Metallised grey

Code example: 0.02043.00 10


T-connector




0.02045.00



0.02046.00



0.02047.00




0.02048.00

Type	
0.02045.00	Earth inside / left
0.02046.00	Earth inside / right
0.02047.00	Earth outside / left
0.02048.00	Earth outside / right

Finishes	
10	White
21	Black
28	Metallised grey

Code example: 0.02045.00 10

X-connector



Finishes	
0.02049.00	10 White
	21 Black
	28 Metallised grey


Code example: 0.02049.00 10

Flexible connector




	Finishes	
0.02050.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02050.00 10




L-connector



X-connector


N.B.



MECHANICAL KEYS
 A mechanical key on the track profile assures correct connection of the track lengths. Live end feeds and connectors also have a mechanical key (with screw - see diagram). This must be taken into account to select the right component.
 In the catalogue drawings of these accessories, the yellow-green line indicates the earthing contact.

ACCESSORIES FOR ELECTROMECHANICAL CONNECTIONS (RECESSED TRACK)



Live end feed cover



	Finishes	
0.02059.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02059.00 10


Live middle feed cover



	Finishes	
0.02060.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02060.00 10

L-connector cover





	Finishes	
0.02056.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02056.00 10

Track



T-connector cover



	Finishes	
0.02057.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02057.00 10

X-connector cover



	Finishes	
0.02058.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02058.00 10

ACCESSORIES (SURFACE-MOUNTED TRACK)

End cap (dead end) for surface-mounted track with locking screw



	Finishes	
0.02041.00	10	White
	21	Black
	28	Metallised grey

Code example: **0.02041.00 10**

Ceiling bracket



	Finishes	
0.02054.00	10	White
	21	Black
	28	Metallised grey

Code example: **0.02054.00 10**

Ceiling clamp



Reference


0.02065.0010

Cable cutter





Reference

0.02064.0000



PENDANT MOUNTING (SURFACE-MOUNTED TRACK)

Suspension set





Composed of:
 - ceiling bracket
 - wire clamp
 - plastic ceiling rose (Ø 32 mm)
 - steel wire (Ø 1.5 mm; L=1500/5000 mm) with M6 terminal

Wire length	
0.02052.00	1500 mm
0.02053.00	5000 mm

Finishes	
10	White
21	Black
28	Metallised grey

Code example: **0.02052.00 10**

Suspension kit with 2-m long wire and counter-balance system




Wire length	
0.25864.00	2000 mm

Finishes	
10	White
21	Black

Esempio codice: **0.25864.00 10**

Track set




Composed of:
 - point clamp suspension M6
 - plastic cover

Finishes	
0.02051.00	10 White
	21 Black
	28 Metallised grey

Code example: **0.02051.00 10**


Short T-bracket for suspension



	Finishes	
0.02055.00	10	White
	21	Black
	28	Metallised grey


Code example: 0.02055.00 10

Clamp with gripper for rapid track installation




	Finishes	
0.02061.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02061.00 10



ADAPTER ACCESSORIES


Monopoint for ceiling mounting of DALI adapter without using the track



	Finishes	
0.02062.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02062.00 10

Adapter for recessed mounting of DALI monopoint (reference 0.02062.00)




	Finishes	
0.02063.00	10	White
	21	Black
	28	Metallised grey

Code example: 0.02063.00 10

Track

BREAKDOWN DIAGRAM



Use specialised technicians only to install systems and replace parts. Disconnect system from power supply and ensure compliance of installation procedure with national standards. The user and/or installer are responsible for ensuring electrical, mechanical and thermal compatibility of the system with the structures where they will be anchored and with regard to the luminaires connected to them.

INDEX

Reference	Page
0.02030.00	8
0.02031.00	8
0.02032.00	8
0.02033.00	8
0.02034.00	8
0.02035.00	8
0.02036.00	8
0.02037.00	8
0.02038.00	9
0.02039.00	9
0.02040.00	9
0.02041.00	14
0.02042.00	9
0.02043.00	10
0.02044.00	10
0.02045.00	10
0.02046.00	10
0.02047.00	10
0.02048.00	10
0.02049.00	10
0.02050.00	11
0.02051.00	16
0.02052.00	16
0.02053.00	16
0.02054.00	14
0.02055.00	17
0.02056.00	12
0.02057.00	13
0.02058.00	13
0.02059.00	12
0.02060.00	12
0.02061.00	17
0.02062.00	18
0.02063.00	18
0.02064.00	15
0.02065.00	14
0.25864.00	16

Worldwide contacts

HEADQUARTERS

ITALY

Reggiani Spa Illuminazione

Viale Monza 16 P.O. Box 99

20845 Sovico (MB), Italy

T. (+39) 039 20711

F. (+39) 039 2071999

contact@reggiani.net

UNITED KINGDOM

Reggiani Ltd

12 Chester Road

Borehamwood

Herts, WD6 1LT - UK

T. (+44) 0208 236 3000

F. (+44) 0208 236 3099

reggiani@reggiani.co.uk

USA

Reggiani Lighting USA, inc.

372 Starke Road

Carlstadt NJ 07072, USA

T. (+1) 201 372 1717

F. (+1) 201 372 1616

info@reggianiusa.com

www.reggianiusa.com

CHINA

Reggiani Ningbo ITG Lighting co. Ltd

Shenjia Village - Qiulai Town - Yinzhou

315010 Ningbo, China

T. (+86) 574 88418655 - 88412627

F. (+86) 574 88364186

info@itglight.com

FRANCE

Showroom

Showroom Bureau Projets

35 Bd. Richard Lenoir, Bastille

75011 Paris, France

T. (+33) 01 43382704

F. (+33) 01 43382720

france@reggiani.net

RUSSIA

Showroom

Kalanchevskaya Street, 16,

Building 1, Room 4A, 129090 Moscow

T. (+7) 495 2690113 - 846 3320266

F. (+7) 495 2690112

russia@reggiani.net

Worldwide distributors

For the worldwide distributors list visit

www.reggiani.net



Reggiani