



IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Recessed luminaire
Name and address of the applicant	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Name and address of the manufacturer	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Name and address of the factory	<input type="checkbox"/> Additional information on page 2 REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	1x33 W Ceramic CoB LEDs, 950 mA, 37 Vdc max, IP20, Class III, used SELV source. Refer to CB Test Report for the entire list of rating covered by the certificate
Trademark (if any)	
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	cod X.DM58B.HQ Refer to CB Test Report for the entire list of variants covered by the certificate
Additional information (if necessary may also be reported on page 2)	<input type="checkbox"/> Additional information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60598-1:2014, IEC 60598-1:2014/AMD1:2017, IEC 60598-2-2:2011 National differences: AU, NZ
As shown in the Test Report Ref. No. which forms part of this Certificate	3505913.50

This CB Test Certificate is issued by the National Certification Body

DEKRA Certification B.V.
Meander 1051, NL-6825 MJ Arnhem, NetherlandsFirmato digitalmente da
MASSIMILIANO TRIULZI

Code	Insulation class	IP degree	Type installation	t _a
cod X.xyz.w	III	IP 20	Recessed ceiling	25 °C

LEGEND

x	Type of luminaire	<p>TM5 = Yori EVO recessed round with visible trim, with spot size 60 mm, with optical lens precision and with power LED</p> <p>UM5 = Yori EVO recessed round with trimless, with spot size 60 mm, with optical lens precision and with power LED</p> <p>BM5 = Yori EVO recessed round with visible trim, with spot size 60 mm, with optical lens precision and with CoB LED</p> <p>CM5 = Yori EVO recessed round with trimless, with spot size 60 mm, with optical lens precision and with CoB LED</p> <p>BM6 = Yori EVO recessed round with visible trim, with spot size 60 mm, with optical lens precision and with CoB LED</p> <p>CM6 = Yori EVO recessed round with trimless, with spot size 60 mm, with optical reflector performance and with CoB LED</p> <p>DM5 = Yori EVO recessed round with visible trim, with spot size 95 mm, with optical lens precision and with CoB LED</p> <p>FM5 = Yori EVO recessed round with trimless, with spot size 95 mm, with optical lens precision and with CoB LED</p> <p>VM5 = Yori EVO recessed round with visible trim, with spot size 95 mm, with optical lens precision and with power LED</p> <p>ZM5 = Yori EVO recessed round with trimless, with spot size 95 mm, with optical lens precision and with power LED</p> <p>DM6 = Yori EVO recessed round with visible trim, with spot size 95 mm, with optical reflector performance and with CoB LED</p> <p>FM6 = Yori EVO recessed round with trimless, with spot size 95 mm, with optical reflector performance and with CoB LED</p> <p>KM5 = Yori EVO recessed square with visible trim, with spot size 60 mm, with optical lens precision and with power LED</p> <p>XM5 = Yori EVO recessed square with trimless, with spot size 60 mm, with optical lens precision and with power LED</p> <p>GM5 = Yori EVO recessed square with visible trim, with spot size 60 mm, with optical lens precision and with CoB LED</p> <p>HM5 = Yori EVO recessed square with trimless, with spot size 60 mm, with optical lens precision and with CoB LED</p> <p>GM6 = Yori EVO recessed square with visible trim, with spot size 60 mm, with optical reflector performance and with CoB LED</p> <p>HM6 = Yori EVO recessed square with trimless, with spot size 60 mm, with optical reflector performance and with CoB LED</p> <p>LM5 = Yori EVO recessed square with visible trim, with spot size 95 mm, with optical lens precision and with CoB LED</p> <p>MM5 = Yori EVO recessed square with trimless, with spot size 95 mm, with optical lens precision and with CoB LED</p> <p>WM5 = Yori EVO recessed square with visible trim, with spot size 95 mm with optical lens precision and with power LED</p> <p>YM5 = Yori EVO recessed square with trimless, with spot size 95 mm, with optical lens precision and with power LED</p> <p>LM6 = Yori EVO recessed square with visible trim, with spot size 95 mm, with optical reflector performance and with CoB LED</p> <p>MM6 = Yori EVO recessed square with trimless, with spot size 95 mm, with optical reflector performance and with CoB LED</p>
---	-------------------	---

x	Type of luminaire	<p>1M5 = Yori EVO recessed square double with visible trim, with spot size 60 mm, with optical lens precision and with power LED</p> <p>2M5 = Yori EVO recessed square double with trimless, with spot size 60 mm, with optical lens precision and with power LED</p> <p>NM5 = Yori EVO recessed square double with visible trim, with spot size 60 mm, with optical lens precision and with CoB LED</p> <p>PM5 = Yori EVO recessed square double with trimless, with spot size 60 mm, with optical lens precision and with CoB LED</p> <p>NM6 = Yori EVO recessed square double with visible trim, with spot size 60 mm, with optical reflector performance and with CoB LED</p> <p>PM6 = Yori EVO recessed square double with trimless, with spot size 60 mm, with optical reflector performance and with CoB LED</p> <p>QM5 = Yori EVO recessed square double with visible trim, with spot size 95 mm, with optical lens precision and with CoB LED</p> <p>RM5 = Yori EVO recessed square double with trimless, with spot size 95 mm, with optical lens precision and with CoB LED</p> <p>3M5 = Yori EVO recessed square double with visible trim, with spot size 95 mm, with optical lens precision and with power LED</p> <p>4M5 = Yori EVO recessed square double with trimless, with spot size 95 mm, with optical lens precision and with power LED</p> <p>QM6 = Yori EVO recessed square double with visible trim, with spot size 95 mm, with optical reflector performance and with CoB LED</p> <p>RM6 = Yori EVO recessed square double with trimless, with spot size 95 mm, with optical reflector performance and with CoB LED</p> <p>FM3 = Yori EVO semi-recessed with spot size 43 mm, with optical lens precision and with CoB LED</p> <p>FM4 = Yori EVO semi-recessed with spot size 43 mm, with optical reflector performance and with CoB LED</p> <p>NM3 = Yori EVO semi-recessed with spot size 60 mm, with optical lens precision and with power LED</p> <p>GM3 = Yori EVO semi-recessed with spot size 60 mm, with optical lens precision and with CoB LED</p> <p>GM4 = Yori EVO semi-recessed with spot size 60 mm, with optical reflector performance and with CoB LED</p> <p>PM3 = Yori EVO semi-recessed with spot size 75 mm, with optical lens precision and with power LED</p> <p>LM3 = Yori EVO semi-recessed with spot size 75 mm, with optical lens precision and with CoB LED</p> <p>LM4 = Yori EVO semi-recessed with spot size 75 mm, with optical reflector performance and with CoB LED</p> <p>QM3 = Yori EVO semi-recessed with spot size 95 mm, with optical lens precision and with power LED</p> <p>MM3 = Yori EVO semi-recessed with spot size 95 mm, with optical lens precision and with CoB LED</p> <p>MM4 = Yori EVO semi-recessed with spot size 95 mm, with optical reflector performance and with CoB LED</p> <p>BD9 = Yori recessed round with trimless, with optical reflector</p> <p>CD9 = Yori recessed round with visible trim, with optical reflector</p> <p>DD9 = Yori recessed square with trimless, with optical reflector</p> <p>FD9 = Yori recessed square with visible trim, with optical reflector</p> <p>GD9 = Yori recessed oval with trimless, with optical reflector</p> <p>HD9 = Yori recessed oval with visible trim, with optical reflector</p> <p>LD9 = Yori recessed rectangular with trimless, with optical reflector</p> <p>MD9 = Yori recessed rectangular with visible trim, with optical reflector</p>
---	-------------------	--

x	Type of luminaire	RD9 = Yori semi-recessed, with optical reflector (recessed hole 55 mm) ND9 = Yori semi-recessed, with optical reflector (recessed hole 110 mm)
y	Type of ratings	2 = 9 W, 700 mA, 12 V max (LED module) 2 = 9 W, 250 mA, 37 V max (CoB LED) 3 = 12 W, 350 mA, 37 V max (CoB LED) 4 = 17 W, 500 mA, 37 V max (CoB LED) 5 = 22 W, 600 mA, 37 V max (CoB LED) 6 = 24 W, 700 mA, 37 V max (CoB LED) 7 = 30 W, 850 mA, 37 V max (CoB LED) 8 = 33 W, 950 mA, 37 V max (CoB LED)
z	Type of beam	A = Very narrow beam B = Narrow beam C = medium-narrow beam D = medium-wide beams E = Medium beam H = Wide beam 1 = with optical reflector cod 0.35005.0000 narrow beams 2 = with optical reflector cod 0.35006.0000 medium beams 3 = with optical reflector cod 0.35007.0000 wide beams K = Without optics
w	Colour temperature with CRI	HW = 2700 K, CRI > 90 WW = 3000 K, CRI > 80 HQ = 3000 K, CRI > 90 HC = 3000 K, CRI > 98 WN = 3500 K, CRI > 80 NN = 4000 K, CRI > 80 HN = 4000 K, CRI > 90 CC = 5000 °K , CRI > 80 CQ = 5000 °K , CRI > 90 DT = 1700 K-3000 K, CRI > 95