



IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME

## CB TEST CERTIFICATE

Product	Recessed luminaire
Name and address of the applicant	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Name and address of the manufacturer	REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Name and address of the factory	<input type="checkbox"/> Additional information on page 2 REGGIANI S.P.A. ILLUMINAZIONE Viale Monza 16 20845 Sovico (MB) Italy
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	220-240 V~, 50/60 Hz, Class I, IP40
Trademark (if any)	
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	cod D.CH050.WW
Additional information (if necessary may also be reported on page 2)	<input type="checkbox"/> Additional information on page 2 Refers to CB Test Report for the entire list of rating covered by the certificate
A sample of the product was tested and found to be in conformity with	IEC 60598-1:2014, IEC 60598-2-2:2011 National differences: EU Group Differences
As shown in the Test Report Ref. No. which forms part of this Certificate	3505211.50

This CB Test Certificate is issued by the National Certification Body

DEKRA Certification B.V.  
Meander 1051, NL-6825 MJ Arnhem, NetherlandsFirmato digitalmente da  
MASSIMILIANO TRIULZI 

Code	Insulation class	Colour temperature	IP degree	t <sub>a</sub>
cod x.y.wwz	I	2700 K CRI>90= HW 3000 K CRI>90 = HQ 3000 K CRI>80 = WW 4000 K CRI>80 = NN	IP40	25 °C

## LEGEND

x	Type of control	0 = Not dimmable D = DALI
y	Type of luminaire	BH020= single model, with diffusive screen, 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x)
		BH050= single model, with diffusive screen, 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x)
		BH070= single model, with diffusive screen, 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x)
		BH0T0= single model, with diffusive screen, 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x)
		CH020= continuous model, with diffusive screen, 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x)
		CH050= continuous model, with diffusive screen, 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x)
		CH070= continuous model, with diffusive screen, 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x)
		CH0T0= continuous model, with diffusive screen, 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x)
		NH020= single model, with Louver screen (UGR<19), 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x)
		NH050= single model, with Louver screen (UGR<19) , 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x)
		NH070= single model, with Louver screen (UGR<19) , 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x)
		NH0T0= single model, with Louver screen (UGR<19) , 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x)
		PH020= continuous model, with Louver screen (UGR<19), 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x)
		PH050= continuous model, with Louver screen (UGR<19) , 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x)
		PH070= continuous model, with Louver screen (UGR<19), 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x)
		PH0T0= continuous model, with Louver screen (UGR<19), 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x)
		GH020= single model, with prismatic screen, 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x)
		GH050= single model, with prismatic screen, 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x)

y	Type of luminaire	GH070=	single model, with prismatic screen, 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x)
		GH0T0=	single model, with prismatic screen, 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x)
		LH020=	continuous model, with prismatic screen, 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x)
		LH050=	continuous model, with prismatic screen, 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x)
		LH070=	continuous model, with prismatic screen, 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x)
		LH0T0=	continuous model, with prismatic screen, 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x)
		KH020=	single model, with ribbed screen, 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x)
		KH050=	single model, with ribbed screen, 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x)
		KH070=	single model, with ribbed screen, 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x)
		KH0T0=	single model, with ribbed screen, 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x)
		RH020=	continuous model, with ribbed screen, 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x)
		RH050=	continuous model, with ribbed screen, 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x)
		RH070=	continuous model, with ribbed screen, 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x)
		RH0T0=	continuous model, with ribbed screen, 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x)
		DH050=	version corner, with diffusive screen, 26 W 200 mA 149 V max, dimension 488x488mm
		QH050=	version corner, with Louver screen (UGR<19), 26 W 200 mA 149 V max, dimension 488x488mm
		MH050=	version corner, with prismatic screen), 26 W 200 mA 149 V max, dimension 488x488mm
		TH050=	version corner, with ribbed screen), 26 W 200 mA 149 V max, dimension 488x488mm
		JLR249-R=	with diffusive screen, 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x), 3000 K
		JLR250-R=	with diffusive screen, 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x) 3000 K
		JLR251-R=	with diffusive screen, 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x) 3000°K
		JLR252-R=	with diffusive screen, 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x) 3000 K
		JLR269-R=	with diffusive screen, 13 W 100 mA 149 V max, length 475mm, length LED module 460 mm (2x) 4000 K
		JLR270-R=	with diffusive screen, 26 W 200 mA 149 V max, length 935mm, length LED module 920 mm (4x) 4000 K
		JLR271-R=	with diffusive screen, 38 W 300 mA 149 V max, length 1395mm, length LED module 1380 mm (6x) 4000 K
		JLR272-R=	with diffusive screen, 58 W 500 mA 149 V max, length 2315mm, length LED module 2300 mm (10x) 4000 K

ww	Type colour temperature and CRI	HW = 2700 K CRI>90 HQ = 3000 K CRI>90 WW = 3000 K CRI>80 NN = 4000 K CRI>80
z	Type of connection	Nothing= Single model N= Continuous model